
JERGUSON®
A PRODUCT OF CLARK-RELIANCE

Top Mount Float Operated *Magnetic Level Switch*

Section:	JS100
Bulletin:	JS100.08
Date:	8/2017

Jerguson's Tri-Magnet Level Switches deliver failure-free performance.




Series JD_ _F

The innovative use of repelling magnetic fields eliminates mechanical elements that are prone to failure in high temperatures, extreme vibration, or simply fatigue over time.

FEATURES

- **Tri-Magnet Switching for Unparalleled Reliability**
- **Vibration Resistant**
- **316 Stainless Steel Trim**
- **Multi-Point Alarm**



Unique 3 magnet latching.
No springs...No problem.


"The new switches are very rugged and dependable, and most importantly, they are mercury-free and safe for the environment. Dealing with spilled mercury is an extremely difficult task, but it is one we don't have to worry about with these new switches. The Jerguson Tri-Magnet Level Switches have been in operation in our facility since May 2007."

-Maintenance Superintendent,
Major Utility Power Generation Plant

The Tri-Magnet Level Switch was endurance tested to over 850,000 cycles without failure.


16633 Foltz Parkway ● Strongsville, OH 44149 USA Telephone: (440) 572-1500 ● Fax: (440) 238-8828
www.jerguson.com ● sales@clark-reliance.com

JERGUSON® LEVEL SWITCHES
THE SWITCH MECHANISM




Principle of Operation: Switch Mechanism

The switch mechanism is based on a unique three-dimensional magnet design where the snap action is accomplished by the utilization of magnetic repulsion and attraction. The primary magnet mounted on the float road causes the secondary magnet to rotate as it passes up and down. The switch magnet is repelled by the secondary and snaps to the opposite side. This causes the cradle to pivot, moving the push rods, which operate the switch contacts. The result is positive snap action interlock switching…**no springs…no spring problems!**



Schematic showing three-magnet system

Type	Choice of Switch Mechanisms Application
X4, X8	**General purpose** - 10 amp mechanisms for general purpose duties up to 480ºF
D4, D8	**High temperature** - 5 amp mechanisms for high temperature applications up to 750ºF
H4, H8	**Hermetically sealed** - 5 amp mechanisms suitable for temperatures up to 480°F, contaminated atmosphere environments and intrinsically safe circuits. All moving parts and contacts enclosed in an inert gas filled stainless steel enclosure.
P4, P8	**Low current** - 0.25 amp gold-plated contact switch mechanism for use in intrinsically safe or low power circuits up to 750ºF
E4, E8	**Encapsulated** - 5 amp switch mechanism is sealed / encapsulated inside alluminum housing, suitable for temperatures to 850°F

4 Contact Type D4, X4, P4, H4, E4
2 x S.P.S.T AA Make on Rise BB Make on Fall  Link for SPDT/SPCO
8 Contact Type D8, X8, P8, H8, E8
D.P.D.T. 4 x S.P.S.T. AA Make on Rise BB Make on Fall  Link for DPDT/DPCO




OUR WARRANTY

All mechanical level devices are warranted free of defects in materials and workmanship for five years from the date of original factory shipment.

If returned within the stated warranty period, and upon factory inspection the cause of the claim is determined to be covered under the warranty, at option, the device will be repaired or replaced without cost to the purchaser (or owner), other than transportation.

Jerguson® shall not be liable for mis-application, labor claims, direct or consequential damage or expense arising from the installation or use of the equipment. There are no other warranties expressed or implied.

DIMENSIONAL AND OPERATING LEVEL DATA



ENCLOSURE DIMENSIONAL DATA

Type	Duty	Height G	Conduit Thread	Switch Adjustment	Weatherproof Rating
SA7, SI7	Explosion-proof	13 1/4"	1" NPT	3 3/8"	NEMA 4 & 7
SA4	Weather-proof	12"	1" NPT	3 3/8"	NEMA 4

MATERIALS OF CONSTRUCTION

Technical Specifications	Designed in accordance with the requirements of B31.1 & B31.3.	
Materials of Construction	Carbon Steel Mounting Flange	Stainless Steel Mounting Flange
Flanges/Fittings	ASTM A105	ASTM A182F316
Float & Trim	316 SS	316 SS

Options:
● Low temperature carbon steel chambers ● Controls to meet NACE requirements ● A comprehensive NDT package

ORDERING INFORMATION[1]

TYPICAL MODEL

JDC1F SA4N 1 X4 D71 L09.50

MATERIAL OF CONSTRUCTION

Carbon Steel

JDC_F Top Mount Float Switch (CS)			
MODEL	SPDT MIN. S.G.[2]	DPDT MIN. S.G.[2]	FLOAT RATING[3]
JDC1F	0.72	0.80	350 PSIG @ 100°F, 275 PSIG @ 750°F
JDC2F	0.60	0.60	300 PSIG @ 100°F, 235 PSIG @ 750°F
JDC3F	0.65	0.69	740 PSIG @ 100°F, 505 PSIG @ 750°F
JDC4F	0.65	0.69	1440 PSIG @ 100°F, 935 PSIG @ 750°F
JDC5F	0.72	0.76	1000 PSIG @ 100°F, 780 PSIG @ 750°F
JDC6F	0.36	0.38	300 PSIG @ 100°F, 235 PSIG @ 750°F
JDC7F	0.47	0.49	750 PSIG @ 100°F, 585 PSIG @ 750°F
JDC8F	0.58	0.60	1000 PSIG @ 100°F, 780 PSIG @ 750°F
JDC9F	0.34	0.35	450 PSIG @ 100°F, 350 PSIG @ 750°F

Stainless Steel

JDS_F Top Mount Float Switch (SS)			
MODEL	SPDT MIN. S.G.[2]	DPDT MIN. S.G.[2]	FLOAT RATING[3]
JDS1F	0.72	0.80	350 PSIG @ 100°F, 275 PSIG @ 750°F
JDS2F	0.60	0.60	300 PSIG @ 100°F, 235 PSIG @ 750°F
JDS3F	0.65	0.69	720 PSIG @ 100°F, 425 PSIG @ 750°F
JDS4F	0.65	0.69	1440 PSIG @ 100°F, 935 PSIG @ 750°F
JDS5F	0.72	0.76	1000 PSIG @ 100°F, 780 PSIG @ 750°F
JDS6F	0.36	0.38	300 PSIG @ 100°F, 235 PSIG @ 750°F
JDS7F	0.47	0.49	750 PSIG @ 100°F, 585 PSIG @ 750°F
JDS8F	0.58	0.60	1000 PSIG @ 100°F, 780 PSIG @ 750°F
JDS9F	0.34	0.35	450 PSIG @ 100°F, 350 PSIG @ 750°F

ENCLOSURE TYPES

Enclosure

Code	Duty	Material of cover	Material of base	Material of pressure	Material of screwed	Maximum number of switches
SA4N	Weather-proof	Aluminum Alloy		316 Stainless Steel	To match chamber material	1-2
SA7F	Explosion-proof Factory Mutual Cl.I,Div.1,Grps B,C &D	Drawn Steel	Aluminum Alloy			

Lowest Switch Trip Point (Rising Level[4])


Length (In inches)

PROCESS CONNECTION

CODE	SIZE	CARBON STEEL RATING[3]	SST RATING[3]	NOTES
D2M	1" NPT	1000 PSIG @ 100°F	1000 PSIG @ 100°F	Requires internal access to attach float (float is larger than 1" NPT)
D71	3" 150# R.F. ASME	285 PSIG @ 100°F	275 PSIG @ 100°F	Model JDC1F/JDS1F only, unless internal access is available
D73	3" 300# R.F. ASME	740 PSIG @ 100°F	720 PSIG @ 100°F	
D76	3" 600# R.F. ASME	1480 PSIG @ 100°F	1440 PSIG @ 100°F	
D91	4" 150# R.F. ASME	285 PSIG @ 100°F	275 PSIG @ 100°F	Model JDC1F/JDS1F on all nozzle schedules, 2F-4F to Sch. 80S
D93	4" 300# R.F. ASME	740 PSIG @ 100°F	720 PSIG @ 100°F	
D96	4" 600# R.F. ASME	1480 PSIG @ 100°F	1440 PSIG @ 100°F	
DB1	6" 150# R.F. ASME	285 PSIG @ 100°F	275 PSIG @ 100°F	Model JDC1F/JDS1F on all nozzle schedules, 6F-9F to Sch. 80S
DB3	6" 300# R.F. ASME	740 PSIG @ 100°F	720 PSIG @ 100°F	
DB6	6" 600# R.F. ASME	1480 PSIG @ 100°F	1440 PSIG @ 100°F	
D7M	3" MNPT	1000 PSIG @ 100°F	1000 PSIG @ 100°F	Model JDC1F/JDS1F only

SWITCH MECHANISM TYPES

Switch Mechanism

		Temp Wet-side °F	AC max. values			DC Max. values			
			VA	Volts	Amps	Watts	Volts	Res. Amps	Ind. Amps
X4	4 Contact  Link for SPDT Two independent single pole single throw contact sets	480	2000	440	10	50	250	10	0.5
D4		750	2000	440	5	50	250	5	0.5
H4		480	2000	440	5	50	250	5	0.5
E4		850	2000	440	5	50	250	5	0.5
P4		750	6	250	0.25	3.6	250	0.25	0.1
X8	8 Contact  Link for DPDT Four independent single pole single throw contact sets	480	2000	440	10	50	250	10	0.5
D8		750	2000	440	5	50	250	5	0.5
H8		480	2000	440	5	50	250	5	0.5
E8		850	2000	440	5	50	250	5	0.5
P8		750	6	250	0.25	3.6	250	0.25	0.1

NUMBER OF SWITCH MECHANISMS

No. of Switches

Specify No. of Switches Requried (1,2)

Notes:


[1] Completed Application Design Sheet Required (JS200.08)

[2] For approximation only, 'Lowest Switch Trip Point' < 12.00". Actual min. SG dependent on the final design.


[3] Final pressure rating of the unit is the lower rating between float & process connection.

[4] Specify rising level switch point for single switch, or upper switch of multi-switch model. Falling level 0.56" below rising level. Refer to sketch on page 3.


JERGUSON® "FIT & FORGET" PRODUCTS PROVIDE THE SOLUTION TO YOUR LIQUID LEVEL CONTROL PROBLEMS



Medium Pressures
ASME Class 150, 300, 600
SG 0.40



High Pressure
ASME Class 900, 1500, 2500
SG 0.40



Direct Mounting
ASME Class 150, 300, 600
SG 0.40

You can rely on us

The Jerguson range of liquid level controls is designed for operation in a wide variety of applications.

Typical Applications

Separators
Compressors
Knock Out Pots
Condensors
De-actuators
Storage Tanks
Service Tanks
Header Tanks
Effluent Sumps & Tanks
Heat Exchanger
Lube Oil Tanks
Water Sumps
Scrubbers
Fractioning Columns
Process Vessels
Condensate Tanks
Drainpots
Accumulators
Flush Vessels
Fuel Tanks
Feedwater Heaters
Surge Drums

Jerguson level switches are used for the control of liquids by companies all over the world.

Shell
Exxon
Amoco
Fluor
Hyundai
Hitachi
British Petroleum
Mobil
Texaco
Ingersoll Rand
Compare
Honeywell
Bechtel
Bellili
Ontario Hydro
Nissaci-Sangyo
Foster Wheeler
Siemens
Mannesmann-Demag
Catalytic
Techni
Technipetrol
Nuovo Pignone
Dresser

JERGUSON®

Authorised Distributor:

NATIONWIDE OIL & GAS

46, Jalan SS 22/21, Damansara Jaya,
47400 Petaling Jaya,
Selangor Darul Ehsan, Malaysia.
Email: nog@nog.com.my
Website: www.nog.com.my

Clark·Reliance®

Instrumentation & Control

JERGUSON® JACOBY·TARBOX® Reliance®



Level Gages
Magnetic Level Gages
Switches & Valves



Sight Flow Indicators
Sight Windows
Eductors



Boiler Level Gages
Remote Level Indicators
Boiler Safety Instruments

Filtration & Purification

ANDERSON® Separator



Gas Coalescing & Filtration
Steam Separators & Traps
Liquid Particle Filtration

Enervac™ INTERNATIONAL ULC



Transformer Oil Purification
SF6 Equipment
Air Dryers

OIL FILTRATION SYSTEMS®



Vacuum Dehydrators
Varnish Removal Systems
Hi & Low Flow Filter Skids

Elements, Internals, Parts & More











www.clark-reliance.com / www.clark-reliance.com/parts

16633 Foltz Parkway ● Strongsville, OH 44149 USA Telephone: (440) 572-1500 ● Fax: (440) 238-8828
www.clark-reliance.com ● sales@clark-reliance.com